

July 31, 2009

SUMMARY OF TESTS PERFORMED

Project Number: 18.04481.16.101

Company: Panasonic Computer Solutions Company
Three Panasonic Way, 2F-12
Secaucus, NJ 07094
Attn: Angela MacNeill

Equipment Tested: Panasonic CF-19

Test Dates: May 2009 – July 2009

Notes: *The test item was evaluated for ability to boot into the Microsoft Windows® XP operating system following each of the tests described within this summary report. A listing of summarized tests and results appear in the accompanying table.*

Report Written By:



Eric Domes
Principal Engineer
Structural Dynamics and Product Assurance Section

Reviewed By:



Jenny Ferren
Manager
Structural Dynamics and Product Assurance Section

Summary of Tests Performed on the Panasonic CF-19

Test Description	Test Parameters	Test Results*
Altitude: Storage/Air Transport	MIL-STD-810G, Method 500.5, Procedure I <ul style="list-style-type: none"> 15,000ft Non-Operating 	Pass [†]
Altitude: Operation/Air Carriage	MIL-STD-810G, Method 500.5, Procedure II <ul style="list-style-type: none"> 15,000ft Operating 	Pass [†]
High Temperature: Storage	MIL-STD-810G, Method 501.5, Procedure I <ul style="list-style-type: none"> 160°F Non-Operating 	Pass [†]
High Temperature: Operation	MIL-STD-810G, Method 501.5, Procedure II <ul style="list-style-type: none"> 140°F Operating 	Pass [†]
High Temperature: Tactical-Standby to Operational	MIL-STD-810G, Method 501.5, Procedure III <ul style="list-style-type: none"> High storage (non-operating) to high operating (test for operation) Test results are for battery operation 	Pass
Low Temperature: Storage	MIL-STD-810G, Method 502.5, Procedure I <ul style="list-style-type: none"> -60°F Non-Operating 	Pass [†]
Low Temperature: Operation	MIL-STD-810G, Method 502.5, Procedure II <ul style="list-style-type: none"> -10°F Operating 	Pass [†]
Temperature Shock	MIL-STD-810G, Method 503.5, Procedure I <ul style="list-style-type: none"> From 200°F to -60°F, three cycles 	Pass [†]
Rain: Blowing	MIL-STD-810G, Method 506.5, Procedure I <ul style="list-style-type: none"> 5.8in/hr rain, 70mph wind, 30 minutes per surface Unit operating 	Pass
Rain: Drip	MIL-STD-810G, Method 506.5, Procedure III <ul style="list-style-type: none"> 15 minute exposure, drip test 	Pass [†]
Humidity	MIL-STD-810G, Method 507.5, Procedure II (Aggravated) <ul style="list-style-type: none"> Temp. cycles 86°F to 140°F; 95%RH 	Pass [†]
Sand and Dust: Dust	MIL-STD-810G, Method 510.5, Procedure I <ul style="list-style-type: none"> Blowing Dust (operating) Operating temperature of 140°F 	Pass [†]
Sand and Dust: Sand	MIL-STD-810G, Method 510.5, Procedure II <ul style="list-style-type: none"> Blowing Sand (operating) Operating temperature of 140°F 	Pass [†]
Explosive Atmosphere	MIL-STD-810G, Method 511.5, Procedure I	Pass [†]
Vibration: General Vibration – operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Panasonic provided conditions (operating) 	Pass [†]
Vibration: General Vibration – non-operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Category 24, general minimal integrity (non-operating) 	Pass [†]
Vibration: Loose Cargo Transportation	MIL-STD-810G, Method 514.6, Procedure II	Pass
Shock: Functional	MIL-STD-810G, Method 516.6, Procedure I <ul style="list-style-type: none"> 40g, 11ms Operating 	Pass [†]

[†] Full details will be provided in SwRI Report Number 18.04481.16.100.FR1

* Test previously performed using comparable MIL-STD-810F procedure. See SwRI Report 18.04481.09.FR2

^ Test previously performed using comparable MIL-STD-810F procedure. See SwRI Report 18.04481.09.201a

Test Description	Test Parameters	Test Results*
Shock: Transit-Drop 48-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 48in height on to 2in plywood – non operating • All drops performed on the same unit 	Pass
Shock: Transit-Drop 60-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 60in height on to 2in plywood – non operating • All drops performed on the same unit that was also subjected to all 48in drops 	Pass
Shock: Transit-Drop 72-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 72in height on to 2in plywood – non operating • All drops performed on the same unit that was also subjected to all 48in and all 60in drops 	Pass
Freeze / Thaw	MIL-STD-810G, Method 524, Procedure III (Rapid Temperature Change) <ul style="list-style-type: none"> • Test effects include condensation 	Pass
Vehicle Vibration	ASTM D4169-04 (99) Schedule E, Truck Assurance Level II, Operating	Pass

* Full details will be provided in SwRI Report Number 18.04481.16.100.FR1